

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Number 1

1. Identification

Product identifier

Product Name Ultralease PET Liquid

Other means of identification

Product Code(s) FG-2473

UN number or ID number 1268

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Release Agent

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

Price Driscoll, 5600 Lower Macungie Rd, Macungie, PA 18062, USA, Phone: +01.610.252.5800, www.smooth-on.com, sds@smooth-on.com

E-mail sds@smooth-on.com

Emergency telephone number

Emergency Telephone Chemtel: US: 1-800.255.3924; International: 1-813.248.0585

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements



Danger

Hazard statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H332 - Harmful if inhaled

H340 - May cause genetic defects

H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/clothing and eve/face protection.

Use only outdoors or in a well-ventilated area.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other information

May be harmful in contact with skin. Causes mild skin irritation. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Trade secret
Naphtha, petroleum, light alkylate	64741-66-8	60 - 95	*
Mineral Spirits	8052-41-3	1 - 20	*
Xylene	1330-20-7	1 - 15	*
Ethylbenzene	100-41-4	<1	*
Trimethylbenzene	25551-13-7	<1	*
2-ethylhexane-1,3-diol	94-96-2	<1	*
Ethyltoluene	25550-14-5	<1	*

FG-2473 Revision date 21-Nov-2024

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. Immediate medical attention is required.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person.

Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid breathing vapors

or mists.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause

redness and irritation.

Effects of Exposure May cause cancer. Mutagenic effects. Causes damage to organs through prolonged or

repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media

Large Fire

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire

extinguishing water must be disposed of in accordance with local regulations.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge

Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing

vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Storage Conditions

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Mineral Spirits	TWA: 100 ppm		
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	-
Xylene	TWA: 20 ppm	TWA: 100 ppm	-
1330-20-7		TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4	Ototoxicant - potential to	TWA: 435 mg/m ³	TWA: 100 ppm
	cause hearing disorders	(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	_
Trimethylbenzene			-
25551-13-7		(vacated) TWA: 125 mg/m ³	

Biological occupational exposure limits

Chemical name	ACGIH
Xylene	0.3 g/g creatinine - urine (total of all isomers of
1330-20-7	Methylhippuric acids) - end of shift
Ethylbenzene	150 mg/g creatinine - urine (Sum of mandelic acid and
100-41-4	phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is

recommended. Wash hands before breaks and immediately after handling the product.

None known

None known

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance
Color
No information available

Property Values Remarks • Method

No data available None known pН None known pH (as aqueous solution) Melting point / freezing point No data available None known Initial boiling point and boiling rangeNo data available None known Flash point > -7.77 °C / 18 °F None known **Evaporation rate** No data available None known

No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Flammability

Lower flammability or explosive No data available

limits

No data available None known Vapor pressure Relative vapor density No data available None known No data available None known Relative density None known Water solubility No data available Solubility(ies) No data available None known No data available **Partition coefficient** None known **Autoignition temperature** No data available None known **Decomposition temperature** None known Kinematic viscosity No data available None known

Kinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other information

Explosive properties

Oxidizing properties

No information available
VOC content
No information available
Liquid Density
No information available
Bulk density
No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes mild skin irritation. May be harmful in contact

with skin.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause

redness and irritation.

<u>Acute toxicity</u> Harmful by inhalation.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 7,578.20 mg/kg

 ATEmix (dermal)
 2,101.70 mg/kg

 ATEmix (inhalation-dust/mist)
 4.35 mg/l

Component Information

Oomponent imormation			
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha, petroleum, light alkylate 64741-66-8	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 6.31 mg/L (Rat) 4 h
Mineral Spirits 8052-41-3	-	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Trimethylbenzene 25551-13-7	= 8970 mg/kg (Rat)	-	-
2-ethylhexane-1,3-diol 94-96-2	= 1400 mg/kg (Rat)	= 8960 mg/kg (Rabbit) = 10251 mg/kg (Rabbit)	> 3.8 mg/L (Rat)4 h
Ethyltoluene 25550-14-5	> 3492 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 6193 mg/m³ (Rat) 4 h
	= 6984 mg/kg (Rat)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for

ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical nar	ne	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	,	-	Group 3	-	-
Ethylbenzer 100-41-4		A3	Group 2B	-	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Target organ effects Kidney, Respiratory system, Eyes, Skin, Central nervous system.

Aspiration hazard May be fatal if swallowed and enters airways.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

	Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ī	Naphtha, petroleum, light alkylate 64741-66-8	EC50: =30000mg/L (72h, Pseudokirchneriella subcapitata)	-	-	LC50: =2mg/L (48h, Mysidopsis bahia)
	Xylene 1330-20-7	EC50: =11mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 -	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h,

	,			
		4.093mg/L (96h,		Gammarus lacustris)
		Oncorhynchus mykiss)		
		LC50: 13.5 - 17.3mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 13.1 - 16.5mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =19mg/L (96h,		
		Lepomis macrochirus)		
		LC50: 7.711 -		
		9.591mg/L (96h,		
		Lepomis macrochirus)		
		LC50: 23.53 -		
		29.97mg/L (96h,		
		Pimephales promelas)		
		LC50: =780mg/L (96h,		
		Cyprinus carpio)		
		LC50: >780mg/L (96h,		
		Cyprinus carpio)		
		LC50: 30.26 -		
		40.75mg/L (96h,		
		Poecilia reticulata)		
Ethylbenzene	EC50: =4.6mg/L (72h,	LC50: 11.0 - 18.0mg/L	-	EC50: 1.8 - 2.4mg/L
100-41-4	Pseudokirchneriella	(96h, Oncorhynchus		(48h, Daphnia magna)
	subcapitata)	mykiss)		
	EC50: >438mg/L (96h,	LC50: =4.2mg/L (96h,		
	Pseudokirchneriella	Oncorhynchus mykiss)		
	subcapitata)	LC50: 7.55 - 11mg/L		
	EC50: 2.6 - 11.3mg/L	(96h, Pimephales		
	(72h,	promelas)		
	Pseudokirchneriella	LC50: =32mg/L (96h,		
	subcapitata)	Lepomis macrochirus)		
	EC50: 1.7 - 7.6mg/L	LC50: 9.1 - 15.6mg/L		
	(96h,	(96h, Pimephales		
	Pseudokirchneriella	promelas)		
	subcapitata)	LC50: =9.6mg/L (96h,		
		Poecilia reticulata)		
Trimethylbenzene	-	LC50: =7.72mg/L (96h,	-	-
25551-13-7		Pimephales promelas)		

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Mineral Spirits	6.4
8052-41-3	
Xylene	3.15
1330-20-7	
Ethylbenzene	3.6
100-41-4	
2-ethylhexane-1,3-diol	3.09
94-96-2	

Other adverse effects

No information available.

FG-2473 Revision date 21-Nov-2024

13. Disposal considerations

Disposal methods

Waste from residues/unused Should not be released into the environment. Dispose of in accordance with local products

regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as

a hazardous waste.

14. Transport information

Regulated DOT

1268 **UN number or ID number** Proper shipping name Petroleum distillates, n.o.s. (Octanes)

Transport hazard class(es) Ш **Packing group**

TDG Regulated **UN number or ID number** 1268

UN proper shipping name Petroleum distillates, n.o.s. (Octanes)

Transport hazard class(es) Packing group Ш

IATA Regulated **UN number or ID number** 1268

UN proper shipping name Petroleum distillates, n.o.s. (Octanes)

Transport hazard class(es) Packing group Ш **ERG Code** 128

IMDG Regulated **UN** number or ID number 1268

UN proper shipping name Petroleum distillates, n.o.s. (Octanes)

Transport hazard class(es) Packing group Ш EmS-No. F-E, S-E **Marine Pollutant** Marine pollutant

15. Regulatory information

International Inventories

TSCA Contact supplier for inventory compliance status. **DSL/NDSL** Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. **EINECS/ELINCS** Contact supplier for inventory compliance status. **ENCS** Contact supplier for inventory compliance status. **IECSC** Contact supplier for inventory compliance status. **KECI PICCS** Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. AIIC **NZIoC** Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AIIC - Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
Xylene - 1330-20-7	1.0	
Ethylbenzene - 100-41-4	0.1	

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	•	CWA - Toxic Pollutants		CWA - Hazardous
	Quantities		Pollutants	Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	Х	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits 8052-41-3	X	X	Х
Xylene	X	X	X

1330-20-7			
Ethylbenzene 100-41-4	X	X	X
Trimethylbenzene 25551-13-7	X	Х	Х
Ethyltoluene 25550-14-5	Х	-	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 0 Instability 0 Special hazards - HMIS Health hazards 2 Flammability 0 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Leaend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date 21-Nov-2024

Revision NoteNo information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Page 13 / 13