

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Number 1

1. Identification

Product identifier

Product Name Ease Release 200, 300, 400, 500, 700, 2300, 2910

Other means of identification

Product Code(s) FG-7040

UN number or ID number 1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Aerosol

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

Mann Release Technologies, Inc. 5600 Lower Macungie Rd., Macungie, PA 18062, Phone (610) 252-5800, FAX (610) 252-6200, www.mann-release.com/, sds@smooth-on.com

E-mail sds@smooth-on.com

Emergency telephone number

Emergency Telephone Chemtel: US: 1-800.255.3924; International: 1-813.248.0585

2. Hazard(s) identification

Classification

Flammable aerosols	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements



Danger

Hazard statements

H223 - Flammable aerosol

H229 - Pressurized container: May burst if heated

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/clothing and eye/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Trade secret
Dimethyl ether	115-10-6	25 - 50	*
1,1-difluoroethane	75-37-6	25 - 50	*
Mineral Spirits	8052-41-3	0.5 - 1.5	*
Xylene	1330-20-7	0.1 - 1	*
Ethylbenzene	100-41-4	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

FG-7040 Revision date 07-Feb-2025

Ingestion Rinse mouth.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Wear

personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure May cause cancer. Mutagenic effects. Causes damage to organs through prolonged or

repeated exposure.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable Extinguishing Media

Large Fire

Dry chemical. Carbon dioxide (CO2). Water spray.

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists.

Containers may explode when heated. Ruptured cylinders may rocket.

Explosion data

Sensitivity to mechanical impact Yes.

Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire

and explosion hazard. Do not cut, puncture or weld containers.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce

vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	ACGIH TLV OSHA PEL	
Mineral Spirits	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	
Xylene	TWA: 20 ppm	TWA: 100 ppm	-
1330-20-7		TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
	(vacated) STEL: 150 pp		
		(vacated) STEL: 655 mg/m ³	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4	Ototoxicant - potential to	TWA: 435 mg/m ³	TWA: 100 ppm
	cause hearing disorders	(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm STEL:	
		(vacated) STEL: 545 mg/m ³	

Biological occupational exposure limits

Chemical name	ACGIH
Xylene	0.3 g/g creatinine - urine (total of all isomers of

1330-20-7	Methylhippuric acids) - end of shift
Ethylbenzene	150 mg/g creatinine - urine (Sum of mandelic acid and
100-41-4	phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Showers **Engineering controls**

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Tight sealing safety goggles. Eye/face protection

Impervious gloves. Wear suitable gloves. Hand protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Skin and body protection

Antistatic boots.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical

> nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Aerosol **Appearance** Aerosol

Color No information available

Odor Slight ethereal

Odor threshold No information available

Property Remarks • Method Values

No data available None known Hq None known pH (as aqueous solution) Melting point / freezing point No data available None known Initial boiling point and boiling range-24.8000 °C / -12.64 °F None known Flash point >= -37 - -41.0000 °C / -34.6 -None known

-41.8 °F

No data available **Evaporation rate** None known **Flammability** No data available None known None known Flammability Limit in Air

Upper flammability or explosive No data available

limits

No data available Lower flammability or explosive

limits

518 mmHg @ 20°C / 70°F Vapor pressure None known Relative vapor density None known Relative density No data available None known Water solubility Negligible None known Solubility(ies) No data available None known **Partition coefficient** No data available None known No data available Autoignition temperature None known **Decomposition temperature** None known Kinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other information

Explosive properties
Oxidizing properties
No information available
VOC content
Liquid Density
No information available
Bulk density
No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of

incompletely burned carbon compounds.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity .

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 4,272.70 mg/kg
ATEmix (inhalation-gas) 442,493.90 ppm
ATEmix (inhalation-dust/mist) 7.83 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Dimethyl ether 115-10-6	-	-	= 164000 ppm (Rat) 4 h	
1,1-difluoroethane 75-37-6	-	-	= 437500 ppm (Rat) 4 h	
Mineral Spirits 8052-41-3	•		> 5.5 mg/L (Rat)4 h	
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h	
Ethylbenzene 100-41-4			= 17.4 mg/L (Rat)4 h	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for

ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Target organ effects Kidney, Respiratory system, Eyes, Skin, Central nervous system.

Aspiration hazard No information available.

Other adverse effects No information available.

Interactive effects

No information available.

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	-
Xylene 1330-20-7	EC50: =11mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	<u>-</u>	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)
Ethylbenzene 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Dimethyl ether	-0.18
115-10-6	
Mineral Spirits	6.4
8052-41-3	
Xylene	3.15
1330-20-7	
Ethylbenzene	3.6
100-41-4	

Other adverse effects

No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local

regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as

a hazardous waste.

14. Transport information

DOT Regulated
UN number or ID number 1950

Proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1

TDG Regulated
UN number or ID number 1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1

IATA Regulated
UN number or ID number UN 1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1

IMDGRegulatedUN number or ID number1950UN proper shipping nameAerosols

Transport hazard class(es) 2.1 EmS-No. F-D, S-U

15. Regulatory information

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Contact supplier for inventory compliance status.

EINECS/ELINCS
Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AllC - Australian Inventory of Industrial Chemicals **NZIOC** - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
Ethylbenzene - 100-41-4	0.1	

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority	CWA - Hazardous
	Quantities		Pollutants	Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	Х	Χ	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

This product contains the following i roposition to chemicals.		
Chemical name	California Proposition 65	
Ethylbenzene - 100-41-4	Carcinogen	

Revision date 07-Feb-2025

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Dimethyl ether 115-10-6	Х	X	X
1,1-difluoroethane 75-37-6	Х	Х	-
Mineral Spirits 8052-41-3	X	X	X
Xylene 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 4 Instability 0 Special hazards - Health hazards 2 Flammability 4 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend

* = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Revision date 07-Feb-2025

Organization for Economic Co-operation and Development High Production Volume Chemicals Program Organization for Economic Co-operation and Development Screening Information Data Set World Health Organization

Revision date 07-Feb-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Page 12 / 12